

# FRESCO

## CONCRETE RIPPER

### CONCRETE SEAL 610

Water repellent sealer, Water-based silane based, complies with standard EN 504-2

#### Short Description:

CONCRETE SEAL 610 is an advanced clear liquid designed to prevent water penetration, especially suitable for exposed concrete surfaces in coastal and high-humidity areas. The product provides maximum protection and durability against harsh weather conditions.

#### Uses:

- Prevents water penetration in exposed concrete and mineral surfaces.
- Specifically designed for reinforced concrete in coastal or high-salt environments.

#### Surface Preparation:

- Clean the surface from dirt, stains, oils, and construction materials.
- Ensure the surface is completely dry before application.

#### Application Instructions:

- Stir the product thoroughly before use.
- Apply using a brush, roller, wet cloth, or spraying device.
- For additional protection, apply a second wet layer over the first wet layer.



Product does not contain copper. Usage of protective gear and proper ventilation is advised. If product touches the eyes, rinse thoroughly and seek medical assistance. Make sure package is properly sealed; do not hang from the handle. Keep away from children. Do not mix with any products not recommended by Fresco. The above recommendations do not substitute professional advice within individual work plans. All details mentioned above are based on research, knowledge and experience obtained during production and usage of the product; they should not be seen as a general, specific, or implied guarantee of any sorts. Our guarantee is for the quality of the product alone, the user must check compatibility with their specific needs. We reserve the right to revise or alter any details without prior notice.

#### Coverage:

0.17-0.12 kg/m<sup>2</sup>, depending on the surface's absorption capabilities.

#### Drying Time:

One hour.

#### Technical Data:

Parameter	Value
Density	0.9-1
Water Resistance	High
Rain Resistance	hours 2-4
Surface Penetration	Approx. 10 mm in two layers

#### Packaging and Storage:

- Volume: 5 liters, 18 liters
- Storage: 12 months in a sealed container in a cool place

#### Safety and Handling Instructions:

- Use gloves, mask, and safety goggles during application.
- In case of contact with skin or eyes, rinse thoroughly with water and seek medical advice if necessary.

#### Compliance and Standards:

Complies with EN 504-2.